

Flexisurf Maintenance & Care

Maintenance: Flexisurf installed indoors with a finish applied in the field, should be cleaned and maintained in accordance with the finish manufacturer's recommendations. Otherwise, maintenance of the floor by damp mopping with a neutral cleaner is preferable. It is acceptable to use a power scrubber or buffer on fully bonded installations following the finish manufacturer's instructions for cleaning. Outdoors, we recommend cleaning Flexisurf with mild detergent, a nylon bristle scrub-brush and water. Ensure all soap residue is rinsed from the Flexisurf before allowing to dry. Power washing using medium pressure nozzles is also an acceptable method for cleaning outdoor installations. Stripping removes strippable floor finish and is required when renewal of finish no longer produces satisfactory results.

Factory Applied Finish: Yemm & Hart recommends Flexisurf with a factory applied urethane finish. The factory applied finish is thicker than what is possible to apply in the field. This finish can last 5 to 10 years with adequate maintenance and care.

Field Applied Finish: Flexisurf can be finished in the field and maintained as part of regular floor maintenance program. Strippable and non-strippable finishes are acceptable. Finish and refinish a floor when there will be no foot traffic. When this is not possible, rope off one part of the floor to be finished to stop foot traffic, remove construction debris, vacuum area thoroughly as well as the surrounding areas. Clean scuffmarks, grease and gum with a cleaner/degreaser.

Care: Exercise care when moving or relocating equipment over Flexisurf sheet or tiles to prevent damage to the floor. Do not scrub or strip fully bonded floors until at least 4 or 5 days after installation to give the Flexisurf enough time to sufficiently bond with the adhesive. The use of pads, wide casters/rollers, furniture/equipment cups may prevent excessive indentation. The performance and guarantee of the products used in preparation, testing, installation and maintenance of Flexisurf, during and after installation, remain with the manufacturer of said product and not Yemm & Hart.

Recommended Finishes: Yemm & Hart recommends for a non-strippable finish Hydroline Wood Floor Finish - Satin 4X0310 vinyl/sports floor finish for the most successful maintenance and care. This catalyzed finish is available from Yemm & Hart. When a strippable finish is preferred, any reputable brand of commercial, floor-care products are acceptable.

Recommended Floor Care Products: The recommended floor care products for Flexisurf installations are included on the Flexisurf website. Other floor care products not specifically recommended by Yemm & Hart may also produce satisfactory results.

Additional Information: Review the Flexisurf Installation guide to gain the detailed information required for successful Flexisurf maintenance and care.

Please contact us if you need further information or help with a specific application.